## NSN 5320-01-599-9833

View Online at https://aerobasegroup.com/nsn/5320-01-599-9833

Pin-rivet - Page 1 of 2



**Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.200 inches **Head Style:** Crown countersunk less than 135 degrees **Head Height:** Between 0.0612 inches and 0.0633 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.334 inches and 0.347 inches Lubrication: Cetyl alcohol **End Application:** C-17a aircraft **Grip Length:** 0.875 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded, 100 degrees fl crown rivet hd Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 federal standard single material response or ams4928 federal standard single material response **Surface Treatment:** Aluminum alloy or chromate **Surface Treatment Specification:** 

Unjf

**Thread Series Designator:** 

Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response

## NSN 5320-01-599-9833

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0