

View Online at <https://aerobasegroup.com/nsn/5320-01-600-2431>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.3665 inches and 0.3865 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.059 inches and 0.069 inches

**Width Between Flats:**

Between 0.316 inches and 0.332 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.387 inches and 0.412 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.3075 inches and 0.3175 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Shear Strength:**

9300 double pounds per square inch

**Countersink Angle:**

45.0 degrees

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0