## NSN 5320-01-600-2431

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-600-2431 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.3665 inches and 0.3865 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.316 inches and 0.332 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.3075 inches and 0.3175 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** 45.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-600-2431

Pin-rivet - Page 2 of 2



Fiig:

A528u0