

View Online at <https://aerobasegroup.com/nsn/5320-01-600-3357>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.200 inches and 0.210 inches

Width Between Flats:

Between 0.306 inches and 0.326 inches

Shank Diameter:

Between 0.560 inches and 0.561 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.5625 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10

Width Across Flats:

Between 0.252 inches and 0.255 inches

Thread Qty Per Inch (tpi):

20.000

Min. Tensile Strength (psi):

43500 pounds per square inch

Shear Strength:

62100 single pounds per square inch

Product Name:

Hi-lok pin

Special Features:

Hi-lok pin, protruding tension head, stainless steel, 1/16 inch grip variation

Material:

Stainless steel

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

-qq-+416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

73197-342 hi-lok production specification manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0