

View Online at <https://aerobasegroup.com/nsn/5320-01-600-3357>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.200 inches and 0.210 inches

**Width Between Flats:**

Between 0.306 inches and 0.326 inches

**Shank Diameter:**

Between 0.560 inches and 0.561 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.5625 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

A-10

**Width Across Flats:**

Between 0.252 inches and 0.255 inches

**Thread Qty Per Inch (tpi):**

20.000

**Min. Tensile Strength (psi):**

43500 pounds per square inch

**Shear Strength:**

62100 single pounds per square inch

**Product Name:**

Hi-lok pin

**Special Features:**

Hi-lok pin, protruding tension head, stainless steel, 1/16 inch grip variation

**Material:**

Stainless steel

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

-qq-+416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

73197-342 hi-lok production specification manufacturers specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0