NSN 5320-01-601-2542

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-601-2542

Fastener Length:
Between 1.088 inches and 1.118 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Head Height:
0.065 inches
Shank Diameter:
Between 0.197 inches and 0.199 inches
Head Major Diameter:
0.313 inches
Grip Length:
Between 0.280 inches and 0.341 inches
Min. Tensile Strength (psi):
1400 pounds per square inch
Shear Strength:
5240 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Visu-lok, fastener, blind internally threaded, externally sleeve flush shear head, self-locking
Material:
Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut
Material Specification:
Qq-s-763 federal specification single material response sleeve or ams 5639 assn standard single material response sleeve or ams 5641
assn standard single material response sleeve
Surface Treatment:
Passivate sleeve or cadmium sleeve
Surface Treatment Specification:
Qq-p*416, type ii, class 2 federal specification single treatment response nut
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):

Mil-s-6758 spec.