## NSN 5320-01-602-4066

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-602-4066 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.883 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.181 inches and 0.184 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3486 inches and 0.3536 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.558 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Hi-shear specification 258 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-602-4066

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0