## NSN 5320-01-602-8353



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-602-8353 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.069 inches **Head Style:** Straight pan **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.181 inches and 0.184 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Collar Outside Diameter:** Between 0.303 inches and 0.307 inches Collarheight: 0.477 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.192 inches and 0.200 inches **Grip Length:** 0.744 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Collar Style:** Threaded break off type Material: Steel comp 4340 **Material Specification:** Ams 6415 assn standard single material response or ams 6349 assn standard single material response or ams 6049 assn standard single material response **Thread Series Designator:** 

N/a

Unjf

Shelf Life:

## NSN 5320-01-602-8353

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0