## NSN 5320-01-603-1435

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-1435

Thread Class:         3a         Fastener Length:         Between 1.455 inches and 1.475 inches         Head Style:         Straight pan         Head Height:         Between 0.130 inches and 0.140 inches         Width Between Flats:         Between 0.1582 inches and 0.1617 inches         Shank Diameter:         Between 0.3896 inches and 0.3901 inches         Shank Style:         Pin-rivet, straight, threaded         Head Major Diameter:         Between 0.565 inches and 0.600 inches         Lubrication:         Solid film or cetyl alcohol         End Application:         F/a-18 e/f         Grip Length:         0.875 inches         Thread Size:         0.3750 inches         Material:         Stainless steel         Material:         Stainless steel         Material Specification:         Ams5629 assn standard single material response
Fastener Length:Between 1.455 inches and 1.475 inchesHead Style:Straight panHead Height:Between 0.130 inches and 0.140 inchesWidth Between Flats:Between 0.1582 inches and 0.1617 inchesShank Diameter:Between 0.3896 inches and 0.3901 inchesShank Style:Pin-rivet, straight, threadedHead Major Diameter:Between 0.565 inches and 0.600 inchesLubrication:Solid film or cetyl alcoholEnd Application:F/a-18 e/fGrip Length:0.375 inchesThready Qty Per Inch (tpi):24Thread Size:0.3750 inchesMaterial:Stainless steelMaterial:Stainless steelMaterial Specification:
Between 1.455 inches and 1.475 inches Head Style: Straight pan Head Height: Between 0.130 inches and 0.140 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches Shank Diameter: Between 0.3896 inches and 0.3901 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.565 inches and 0.600 inches Lubrication: Solid film or cetyl alcohol End Application: F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel
Head Style:Straight panHead Height:Between 0.130 inches and 0.140 inchesWidth Between Flats:Between 0.1582 inches and 0.1617 inchesShank Diameter:Between 0.3896 inches and 0.3901 inchesShank Style:Pin-rivet, straight, threadedHead Major Diameter:Between 0.565 inches and 0.600 inchesLubrication:Solid film or cetyl alcoholEnd Application:F/a-18 e/fGrip Length:0.875 inchesThready Qty Per Inch (tpi):24StainelsMaterial:Stainless steelMaterial Specification:
Straight pan Head Height: Between 0.130 inches and 0.140 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches Shank Diameter: Between 0.3896 inches and 0.3901 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.565 inches and 0.600 inches Lubrication: Solid film or cetyl alcohol End Application: F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Head Height:Between 0.130 inches and 0.140 inchesWidth Between Flats:Between 0.1582 inches and 0.1617 inchesShank Diameter:Between 0.3896 inches and 0.3901 inchesShank Style:Pin-rivet, straight, threadedHead Major Diameter:Between 0.565 inches and 0.600 inchesLubrication:Solid film or cetyl alcoholEnd Application:F/a-18 e/fGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Thread Size:0.3750 inchesMaterial:Stainless steelMaterial Specification:
Between 0.130 inches and 0.140 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches Shank Diameter: Between 0.3896 inches and 0.3901 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.565 inches and 0.600 inches Lubrication: Solid film or cetyl alcohol End Application: F/a-18 e/f Grip Length: 0.875 inches Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Width Between Flats:Between 0.1582 inches and 0.1617 inchesShank Diameter:Between 0.3896 inches and 0.3901 inchesShank Style:Pin-rivet, straight, threadedHead Major Diameter:Between 0.565 inches and 0.600 inchesLubrication:Solid film or cetyl alcoholEnd Application:F/a-18 e/fGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Thread Size:0.3750 inchesMaterial:Stainless steelMaterial Specification:
Between 0.1582 inches and 0.1617 inches Shank Diameter: Between 0.3896 inches and 0.3901 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.565 inches and 0.600 inches Lubrication: Solid film or cetyl alcohol End Application: F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Shank Diameter:Between 0.3896 inches and 0.3901 inchesShank Style:Pin-rivet, straight, threadedHead Major Diameter:Between 0.565 inches and 0.600 inchesLubrication:Solid film or cetyl alcoholEnd Application:F/a-18 e/fGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Thread Size:0.3750 inchesMaterial:Stainless steelMaterial Specification:
Between 0.3896 inches and 0.3901 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.565 inches and 0.600 inches Lubrication: Solid film or cetyl alcohol End Application: F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Shank Style:Pin-rivet, straight, threadedHead Major Diameter:Between 0.565 inches and 0.600 inchesLubrication:Solid film or cetyl alcoholEnd Application:F/a-18 e/fGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Thread Size:0.3750 inchesMaterial:Stainless steelMaterial Specification:
Pin-rivet, straight, threaded Head Major Diameter: Between 0.565 inches and 0.600 inches Lubrication: Solid film or cetyl alcohol End Application: F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Head Major Diameter:Between 0.565 inches and 0.600 inchesLubrication:Solid film or cetyl alcoholEnd Application:F/a-18 e/fGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Thread Size:0.3750 inchesMaterial:Stainless steelMaterial Specification:
Between 0.565 inches and 0.600 inches Lubrication: Solid film or cetyl alcohol End Application: F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Lubrication: Solid film or cetyl alcohol End Application: F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Solid film or cetyl alcohol End Application: F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
End Application: F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
F/a-18 e/f Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
0.875 inches Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Thready Qty Per Inch (tpi): 24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
24 Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
Thread Size: 0.3750 inches Material: Stainless steel Material Specification:
0.3750 inches Material: Stainless steel Material Specification:
Material: Stainless steel Material Specification:
Stainless steel Material Specification:
Material Specification:
-
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:

## NSN 5320-01-603-1435

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

