

View Online at <https://aerobasegroup.com/nsn/5320-01-603-8306>

Thread Class:

3a

Fastener Length:

Between 2.139 inches and 2.159 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.039 inches and 0.041 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

Lubrication:

Cetyl alcohol

End Application:

Various c5 918s

Grip Length:

1.875 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Pin-threaded, flush crown head, steel, shear type, 1/32" grip variation

Special Features:

Heat treat s-108ksi per mil-h-6875 head is hex drive socket countersunk

Material:

Steel

Material Specification:

Alloy steel per mil-s-500 (4340) or mil-s-6049(8740) military standard all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0