

View Online at <https://aerobasegroup.com/nsn/5320-01-603-8306>

**Thread Class:**

3a

**Fastener Length:**

Between 2.139 inches and 2.159 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.039 inches and 0.041 inches

**Shank Diameter:**

Between 0.1625 inches and 0.1635 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.2564 inches and 0.2612 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

Various c5 918s

**Grip Length:**

1.875 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Pin-threaded, flush crown head, steel, shear type, 1/32" grip variation

**Special Features:**

Heat treat s-108ksi per mil-h-6875 head is hex drive socket countersunk

**Material:**

Steel

**Material Specification:**

Alloy steel per mil-s-500 (4340) or mil-s-6049 (8740) military standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0