## NSN 5320-01-603-8527

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-8527

## Thread Class:

3a

## Fastener Length:

Between 1.440 inches and 1.460 inches

## Head Style:

Straight pan

#### Head Height:

Between 0.104 inches and 0.119 inches

## Shank Diameter:

Between 0.2172 inches and 0.2182 inches

## Shank Style:

Stump

Head Major Diameter:

Between 0.3253 inches and 0.3303 inches

## Chamfer Length:

0.015 inches

Tip Diameter:

Between 0.104 inches and 0.119 inches

## Grip Length:

Between 1.115 inches and 1.135 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

2000 pounds per square inch

Thread Size:

10.0 millimeters

#### **Product Name:**

100 degree flush shear head alloy steel

## Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

## Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military

specification single material response

#### Surface Treatment:

Cadmium

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-603-8527

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

