## NSN 5320-01-603-8565

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-8565 **Thread Class:** За Fastener Length: Between 1.315 inches and 1.335 inches **Head Style:** Straight pan **Head Height:** Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.2172 inches and 0.2182 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.3253 inches and 0.3303 inches **Chamfer Length:** 0.015 inches Tip Diameter: Between 0.104 inches and 0.119 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch **Thread Size:** 10.0 millimeters **Product Name:** 100 degree flush shear head alloy steel Material: Steel comp 4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2, color: bronze, and cetyl-alcohol lube per iii shear spec-305 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-603-8565

Pin-rivet - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.