

View Online at <https://aerobasegroup.com/nsn/5320-01-603-8607>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.201 inches and 2.221 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.039 inches and 0.041 inches

**Width Between Flats:**

Between 0.063 inches and 0.064 inches

**Shank Diameter:**

Between 0.162 inches and 0.163 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.256 inches and 0.261 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-5 aircraft

**Grip Length:**

1.937 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Pin-threaded, flush crown head, stl, shear typ 1/32 grip

**Material:**

Steel comp 430 or steel comp 8740

**Material Specification:**

Mil-s-5000 military standard single material response or mil-s-6049 military standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.