

View Online at <https://aerobasegroup.com/nsn/5320-01-603-8607>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.201 inches and 2.221 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.039 inches and 0.041 inches

Width Between Flats:

Between 0.063 inches and 0.064 inches

Shank Diameter:

Between 0.162 inches and 0.163 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.256 inches and 0.261 inches

Lubrication:

Cetyl alcohol

End Application:

C-5 aircraft

Grip Length:

1.937 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Pin-threaded, flush crown head, stl, shear typ 1/32 grip

Material:

Steel comp 430 or steel comp 8740

Material Specification:

Mil-s-5000 military standard single material response or mil-s-6049 military standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.