# NSN 5320-01-603-8632

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-8632

## Fastener Length:

Between 0.5025 inches and 0.5225 inches

## Head Style:

Straight pan

## Head Height:

Between 0.055 inches and 0.074 inches

## Shank Diameter:

Between 0.2016 inches and 0.2026 inches

#### Shank Style:

Stump

## Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Chamfer Length:

Between 0.020 inches and 0.039 inches

## Tip Diameter:

Between 0.104 inches and 0.119 inches

## Grip Length:

Between 0.1870 inches and 0.1880 inches

## Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

1240 pounds per square inch

## Thread Size:

10.0 millimeters

## **Special Features:**

Heat treat: age to t6 condition per mil-h-6088

Material:

Aluminum alloy 7075

## **Material Specification:**

Qq-a225/9 or qq-a-430 federal specification single material response

## Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625, dye color natural, and cetyl alcohol lubrication per hi-shear specification 305 military specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-603-8632

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-a-8625 spec.

