NSN 5320-01-603-8691

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-8691 Fastener Length: Between 0.565 inches and 0.585 inches **Head Style:** Straight pan **Head Height:** Between 0.055 inches and 0.074 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.295 inches and 0.315 inches **Chamfer Length:** Between 0.020 inches and 0.039 inches **Tip Diameter:** Between 0.104 inches and 0.119 inches **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 1240 pounds per square inch **Thread Size:** 10.0 millimeters **Product Name:** Protruding shear head aluminum alloy **Special Features:** Heat treat: age to t6 condition per mil-h-6088 Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, dye color: natural, and cetyl alcohol lubrication per hi-shear specification 305 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-603-8691

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.