

View Online at <https://aerobasegroup.com/nsn/5320-01-603-8765>

**Thread Class:**

3a

**Fastener Length:**

Between 0.740 inches and 0.760 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.045 inches and 0.055 inches

**Shank Diameter:**

Between 0.2172 inches and 0.2182 inches

**Shank Style:**

Stump

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Chamfer Length:**

0.0312 inches

**Tip Diameter:**

0.104 inches

**Grip Length:**

Between 0.370 inches and 0.380 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

2500 pounds per square inch

**Thread Size:**

10.0 millimeters

**Product Name:**

Protruding shear head alloy steel 1/16 inch grip

**Material:**

Steel

**Material Specification:**

Mil-s-5000 military specification single material response or mils-s-5626 military specification single material response or mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2, color: bronze and cetyl alcohol lubrication per hi-shear specification 305 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.