
# NSN 5320-01-603-8765

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

# Fastener Length:

Between 0.740 inches and 0.760 inches

# Head Style:

Straight pan

#### **Head Height:**

Between 0.045 inches and 0.055 inches

#### Shank Diameter:

Between 0.2172 inches and 0.2182 inches

#### Shank Style:

Stump

Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### Chamfer Length:

# 0.0312 inches

**Tip Diameter:** 

0.104 inches

# Grip Length:

Between 0.370 inches and 0.380 inches

### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

2500 pounds per square inch

#### **Thread Size:**

10.0 millimeters

#### **Product Name:**

Protruding shear head alloy steel 1/16 inch grip

#### Material:

Steel

#### **Material Specification:**

Mil-s-5000 military specification single material response or mils-s-5626 military specification single material response or mil-s-6049 military

specification single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type 2, class 2, color: bronze and cetyl alcolhol lubrication per hi-shear specification 305 federal specification single treatment response

### Thread Series Designator:

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5320-01-603-8765

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

