## NSN 5320-01-603-8798

Pin-rivet - Page 1 of 2





Thread Class:

3a

Fastener Length:

Between 1.440 inches and 1.460 inches

Head Style:

Straight pan

Head Height:

Between 0.045 inches and 0.055 inches

### Shank Diameter:

Between 0.2172 inches and 0.2182 inches

Shank Style:

Stump

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Chamfer Length:

0.0312 inches

Tip Diameter:

Between 0.104 inches and 0.119 inches

Grip Length:

Between 1.120 inches and 1.130 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2500 pounds per square inch

**Product Name:** 

Protruding shear head alloy steel 1/16 inch grip variation 1/32 inch oversize

Material:

Steel

### Material Specification:

Mil-d-5000 mfr ref 15th material response or mil-s-5626 military specification single material response or mil-s-6409 military specification

single material response

Surface Treatment:

Cadmium

### Surface Treatment Specification:

Qq-p-416, type 2, class 2, color: bronze and cetyl alcohol lubrication per hi-shear specification 305 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

# NSN 5320-01-603-8798

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-d-5000 spec.

