NSN 5320-01-603-8823

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-8823

Thread Class:

3a

Fastener Length:

Between 1.615 inches and 1.635 inches

Head Style:

Straight pan

Head Height:

Between 0.068 inches and 0.078 inches

Shank Diameter:

Between 0.3422 inches and 0.3432 inches

Shank Style:

Stump

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Chamfer Length:

0.0468 inches

Tip Diameter:

Between 0.160 inches and 0.180 inches

Grip Length:

Between 1.120 inches and 1.130 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

6300 pounds per square inch

Product Name:

Protruding shear head alloy steel 1/16 inch grip variation 1/32 inch oversize

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2, color: bronxe, and cetyl alcohol lubrication per hi-shear specification 305 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5320-01-603-8823

Pin-rivet - Page 2 of 2

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

