NSN 5320-01-603-8862

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-8862 **Thread Class:** За Fastener Length: Between 1.740 inches and 1.760 inches **Head Style:** Straight pan **Head Height:** Between 0.068 inches and 0.078 inches **Shank Diameter:** Between 0.3422 inches and 0.3432 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.475 inches and 0.505 inches **Chamfer Length:** 0.0468 inches **Tip Diameter:** Between 0.160 inches and 0.180 inches **Grip Length:** Between 1.245 inches and 1.255 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 6300 pounds per square inch **Thread Size:** 0.3125 inches **Product Name:** Protruding shear head alloy steel 1/16 inch grip variation 1/32 oversize Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2, color: bronze, and cetyl alcohol lubrication per hi-shear specification 305 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-603-8862

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.