NSN 5320-01-603-8974

View Online at https://aerobasegroup.com/nsn/5320-01-603-8974

Pin-rivet - Page 1 of 2

Unjf

N/a

Shelf Life:



Thread Class: За Fastener Length: Between 1.4225 inches and 1.4425 inches **Head Style:** Straight pan **Head Height:** Between 0.0658 inches and 0.0679 inches **Shank Diameter:** Between 0.3422 inches and 0.3432 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.5001 inches and 0.5051 inches **Chamfer Length:** 0.0468 inches **Tip Diameter:** Between 0.160 inches and 0.180 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.9325 inches and 0.9425 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 5000 pounds per square inch **Thread Size:** 0.3125 inches **Product Name:** 100 degree flush shear head alloy steel 1/16 inch grip variation, 1/32 inch oversize Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6409 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2, color: bronze and cetyl alcohol lube per hi-shear specification 305 federal specification single treatment response **Thread Series Designator:**

NSN 5320-01-603-8974

Pin-rivet - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.