NSN 5320-01-603-8985

View Online at https://aerobasegroup.com/nsn/5320-01-603-8985

Pin-rivet - Page 1 of 2



Thread Class: За Fastener Length: Between 0.9975 inches and 1.1175 inches **Head Style:** Straight pan **Head Height:** Between 0.130 inches and 0.140 inches **Shank Diameter:** Between 0.4047 inches and 0.4057 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.550 inches and 0.585 inches **Chamfer Length:** 0.0468 inches **Tip Diameter:** Between 0.197 inches and 0.217 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.5575 inches and 0.5675 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 14000 pounds per square inch **Thread Size:** 0.375 inches **Product Name:** Protruding tension head alloy steel 1/16 inch grip variation, 1/32 inch oversize Material: Steel **Material Specification:** Ams-s-6048 assn standard single material response or ams6322 assn standard single material response or ams6349 assn standard single material response or ams6382 assn standard single material response **Surface Treatment:** Cadmium

Ams-qq-p-416, type 2, class 2, cetyl alcohol lube per hi-shear specification 305 assn standard single treatment response

Unjf Shel

Shelf Life:

Surface Treatment Specification:

Thread Series Designator:

N/a

NSN 5320-01-603-8985

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0