## NSN 5320-01-603-9013

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-9013 **Thread Class:** За Fastener Length: Between 1.4275 inches and 1.4475 inches **Head Style:** Straight pan **Head Height:** Between 0.058 inches and 0.069 inches **Shank Diameter:** Between 0.2641 inches and 0.2651 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.387 inches and 0.412 inches **Chamfer Length:** 0.0312 inches **Tip Diameter:** Between 0.122 inches and 0.142 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.4325 inches and 1.4425 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Product Name:** Protruding shear head alloy steel 1/16 inch grip variation, 1/64 inch oversize Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2, and cetyl alcohol lube per hi-shear specification 305 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5320-01-603-9013

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.