# NSN 5320-01-603-9013

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-9013

# Thread Class:

3a

# Fastener Length:

Between 1.4275 inches and 1.4475 inches

## Head Style:

Straight pan

### Head Height:

Between 0.058 inches and 0.069 inches

#### Shank Diameter:

Between 0.2641 inches and 0.2651 inches

#### Shank Style:

Stump

Head Major Diameter:

Between 0.387 inches and 0.412 inches

## Chamfer Length:

0.0312 inches

## Tip Diameter:

Between 0.122 inches and 0.142 inches

## Lubrication:

Cetyl alcohol

## Grip Length:

Between 1.4325 inches and 1.4425 inches

## Thready Qty Per Inch (tpi):

28

# Thread Size:

0.250 inches

## **Product Name:**

Protruding shear head alloy steel 1/16 inch grip variation, 1/64 inch oversize

## Material:

Steel

## **Material Specification:**

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military

specification single material response

### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type 2, class 2, and cetyl alcohol lube per hi-shear specification 305 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5320-01-603-9013

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

