NSN 5320-01-603-9028

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-9028

Thread Class: 3a Fastener Length: Between 1.6775 inches and 1.6975 inches **Head Style:** Straight pan **Head Height:** Between 0.068 inches and 0.078 inches Shank Diameter: Between 0.3266 inches and 0.3276 inches Shank Style: Stump Head Major Diameter: Between 0.475 inches and 0.505 inches **Chamfer Length:** 0.0468 inches **Tip Diameter:** Between 0.180 inches and 0.190 inches Lubrication: Cetyl alcohol Grip Length: Between 1.1825 inches and 1.1925 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 6300 pounds per square inch **Thread Size:** 0.3125 inches **Product Name:** Protruding shear head alloy steel 1/16 inch grip variation, 1/64 inch oversize Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response Surface Treatment: Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2, and cetyl alcohol lube per hi-shear specification 305 federal specification single treatment response **Thread Series Designator:**

Unjf

- Shelf Life:
- N/a

NSN 5320-01-603-9028

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

