

View Online at <https://aerobasegroup.com/nsn/5320-01-603-9028>

Thread Class:

3a

Fastener Length:

Between 1.6775 inches and 1.6975 inches

Head Style:

Straight pan

Head Height:

Between 0.068 inches and 0.078 inches

Shank Diameter:

Between 0.3266 inches and 0.3276 inches

Shank Style:

Stump

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Chamfer Length:

0.0468 inches

Tip Diameter:

Between 0.180 inches and 0.190 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 1.1825 inches and 1.1925 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

6300 pounds per square inch

Thread Size:

0.3125 inches

Product Name:

Protruding shear head alloy steel 1/16 inch grip variation, 1/64 inch oversize

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2, and cetyl alcohol lube per hi-shear specification 305 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.