## NSN 5320-01-603-9222

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-9222 **Thread Class:** За Fastener Length: Between 0.9475 inches and 0.9675 inches **Head Style:** Flush countersunk **Head Height:** Between 0.0523 inches and 0.0544 inches **Shank Diameter:** Between 0.2641 inches and 0.2651 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.3898 inches and 0.3948 inches **Chamfer Length:** 0.0312 inches **Tip Diameter:** Between 0.122 inches and 0.142 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.5575 inches and 0.5675 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Product Name:** 100 degree fulsh shear head alloy steel 1/16 inch grip variation, 1/6 inch oversize Material: Steel **Material Specification:** Ams6415 assn standard single material response or ams6349 assn standard single material response or ams-s-6049 assn standard single material response **Surface Treatment:** Cadmium

Ams-qq-p-416, type 2, class 2, and cetyl alcohol lube per hi-shear specification 305 assn standard single treatment response

Unjf

Shelf Life:

**Surface Treatment Specification:** 

**Thread Series Designator:** 

N/a

## NSN 5320-01-603-9222

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0