## NSN 5320-01-603-9295

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-9295 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.0725 inches and 1.0925 inches **Head Style:** Flush countersunk **Head Height:** Between 0.0993 inches and 0.1013 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2646 inches and 0.2651 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5018 inches and 0.5066 inches **Chamfer Length:** 0.03125 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.6825 inches and 0.6925 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 10490 double pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** 100 degrees flush ms24694 tension head a-286 high temperature alloy 1/16" grip variation-1/64"oversize Material: Iron alloy 660

**Material Specification:** 

A-286 high temp alloy per ams5737 or ams5731 mfr ref single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Passivate per hi-sheer spec.258 mfr ref single treatment response

## NSN 5320-01-603-9295

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A528u0