

View Online at <https://aerobasegroup.com/nsn/5320-01-603-9362>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.0725 inches and 1.0925 inches

Head Style:

Flush countersunk

Head Height:

Between 0.0930 inches and 0.0950 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2802 inches and 0.2807 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

Chamfer Length:

0.03125 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.6825 inches and 0.6925 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

11800 double pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

100 degrees flush ms24694 tension head a-286 high temperature alloy 1/16" griip variation-1/32"oversize

Material:

Iron alloy 660

Material Specification:

A-286 high temp alloy per ams5737 or ams5731 mfr ref single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Passivate per hi-sheer spec.258 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0