

View Online at <https://aerobasegroup.com/nsn/5320-01-603-9362>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.0725 inches and 1.0925 inches

**Head Style:**

Flush countersunk

**Head Height:**

Between 0.0930 inches and 0.0950 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2802 inches and 0.2807 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.5018 inches and 0.5066 inches

**Chamfer Length:**

0.03125 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.6825 inches and 0.6925 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Shear Strength:**

11800 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

100 degrees flush ms24694 tension head a-286 high temperature alloy 1/16" griip variation-1/32" oversize

**Material:**

Iron alloy 660

**Material Specification:**

A-286 high temp alloy per ams5737 or ams5731 mfr ref single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Passivate per hi-sheer spec.258 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0