NSN 5320-01-603-9362

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-603-9362

View Online at https://aerobasegroup.com/nsn/5320-01-603-9362
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.0725 inches and 1.0925 inches
Head Style:
Flush countersunk
Head Height:
Between 0.0930 inches and 0.0950 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2802 inches and 0.2807 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.5018 inches and 0.5066 inches
Chamfer Length:
0.03125 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.6825 inches and 0.6925 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Shear Strength:
11800 double pounds per square inch
Countersink Angle:
100.0 degrees
Product Name:
100 degrees flush ms24694 tension head a-286 high temperature alloy 1/16"griip variation-1/32"oversize
Material:
Iron alloy 660
Material Specification:
A-286 high temp alloy per ams5737 or ams5731 mfr ref single material response
Surface Treatment:
Passivate

Passivate per hi-sheer spec.258 mfr ref single treatment response

NSN 5320-01-603-9362

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A528u0