

View Online at <https://aerobasegroup.com/nsn/5320-01-604-1548>

**Thread Class:**

3a

**Fastener Length:**

2.086 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

0.040 inches

**Shank Diameter:**

Between 0.1625 inches and 0.1635 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.2564 inches and 0.2612 inches

**End Application:**

Various c5 918s

**Grip Length:**

1.812 inches 0.1635 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-threaded, flush crown head, steel, shear type, 1/32 inch grip variation

**Special Features:**

Heat treat/spherical crown w/hex drive socket at tip

**Material:**

Steel

**Material Specification:**

Alloy steel iaw mil-s-500 (4340) or mil-s-6049(8740) military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.