

View Online at <https://aerobasegroup.com/nsn/5320-01-604-1548>

Thread Class:

3a

Fastener Length:

2.086 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

0.040 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

End Application:

Various c5 918s

Grip Length:

1.812 inches 0.1635 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-threaded, flush crown head, steel, shear type, 1/32 inch grip variation

Special Features:

Heat treat/spherical crown w/hex drive socket at tip

Material:

Steel

Material Specification:

Alloy steel iaw mil-s-500 (4340) or mil-s-6049(8740) military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.