## NSN 5320-01-604-1548

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-604-1548 **Thread Class:** За Fastener Length: 2.086 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** 0.040 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2564 inches and 0.2612 inches **End Application:** Various c5 918s **Grip Length:** 1.812 inches 0.1635 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-threaded, flush crown head, steel, shear type, 1/32 inch grip variation **Special Features:** Heat treat/spherical crown w/hex drive socket at tip Material: Steel **Material Specification:** Alloy steel iaw mil-s-500 (4340) or mil-s-6049(8740) military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty ii, cl 2 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-604-1548

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.