NSN 5320-01-604-6092

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-604-6092

Fastener Length:
Between 0.490 inches and 0.510 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.186 inches and 0.190 inches
Shank Style:
Straight with tapered tip
Head Major Diameter:
Between 0.349 inches and 0.357 inches
Chamfer Length:
0.047 inches
Tip Diameter:
Between 0.139 inches and 0.143 inches
End Application:
C130k
Grip Length:
0.070 inches
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Product Name:
Rivet, solid, cuntersunk 100 degree pricision head, aluminum and titanium columbium alloy
Special Features:
Material: 2024-t4 al alloy
Material:
Aluminum alloy 2024
Material Specification:
Ms20426 military specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2, class 1, dichromate seal military specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
<u>-</u>
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
spec.