NSN 5320-01-605-9092

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-605-9092

Fastener Length:

Between 20.400 millimeters and 20.900 millimeters

Head Style:

Straight pan

Head Height:

Between 1.950 millimeters and 2.200 millimeters

Shank Diameter:

Between 7.962 millimeters and 7.987 millimeters

Shank Style:

Stump

Head Major Diameter:

Between 12.250 millimeters and 12.850 millimeters

Chamfer Length:

1.2 millimeters

Tip Diameter:

Between 4.05 millimeters and 4.60 millimeters

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Future lynx helicopter

Grip Length:

Between 10.750 millimeters and 11.250 millimeters

Min. Tensile Strength (psi):

32600 newtons per square millimeter

Shear Strength:

65800 double newtons per square millimeter

Product Name:

Protruding shear head titanium 1mm grip variation

Material:

Titanium alloy

Material Specification:

Ams49284jgaams4967 assn standard single material response or ams4971 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-shear spec. 305 mfr ref single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-605-9092

Pin-rivet - Page 2 of 2

Fiig: A528u0

