

View Online at <https://aerobasegroup.com/nsn/5320-01-605-9092>

**Fastener Length:**

Between 20.400 millimeters and 20.900 millimeters

**Head Style:**

Straight pan

**Head Height:**

Between 1.950 millimeters and 2.200 millimeters

**Shank Diameter:**

Between 7.962 millimeters and 7.987 millimeters

**Shank Style:**

Stump

**Head Major Diameter:**

Between 12.250 millimeters and 12.850 millimeters

**Chamfer Length:**

1.2 millimeters

**Tip Diameter:**

Between 4.05 millimeters and 4.60 millimeters

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

Future lynx helicopter

**Grip Length:**

Between 10.750 millimeters and 11.250 millimeters

**Min. Tensile Strength (psi):**

32600 newtons per square millimeter

**Shear Strength:**

65800 double newtons per square millimeter

**Product Name:**

Protruding shear head titanium 1mm grip variation

**Material:**

Titanium alloy

**Material Specification:**

Ams49284jgaams4967 assn standard single material response or ams4971 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Hi-shear spec. 305 mfr ref single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0