## NSN 5320-01-606-0583

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-606-0583

Fastener Length:
Between 0.521 inches and 0.541 inches
Head Style:
Countersunk w/ reverse chamfer
Head Height:
0.051 inches
Shank Diameter:
Between 0.186 inches and 0.189 inches
Shank Style:
Straight
Head Major Diameter:
0.258 inches
Min. Tensile Strength (psi):
65000 pounds per square inch
Minimum Yield Strength:
60000 pounds per square inch
Shear Strength:
50000 single pounds per square inch
Countersink Angle:
Between 118.5 degrees and 121.5 degrees
Heat Treatment:
Annealed
Material:
Titanium alloy uns r58450
Material Specification:
Ams 4982 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Surface Treatment Specification:  Mil-a8625 military specification single treatment response
•
Mil-a8625 military specification single treatment response
Mil-a8625 military specification single treatment response  Shelf Life:
Mil-a8625 military specification single treatment response  Shelf Life: N/a
Mil-a8625 military specification single treatment response  Shelf Life: N/a
Mil-a8625 military specification single treatment response  Shelf Life:  N/a  Unit Of Measure:
Mil-a8625 military specification single treatment response  Shelf Life: N/a Unit Of Measure: Demilitarization:
Mil-a8625 military specification single treatment response  Shelf Life: N/a Unit Of Measure: Demilitarization: No
Mil-a8625 military specification single treatment response  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: