

View Online at <https://aerobasegroup.com/nsn/5320-01-607-1361>

Thread Class:

3b

Thread Direction:

Right-hand

Identification Code Color:

Red

Fastener Length:

Between 0.690 inches and 0.710 inches

Head Style:

Cooper's

Head Height:

Between 0.039 inches and 0.042 inches

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.2021 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.296 inches and 0.302 inches

Collar Outside Diameter:

Between 0.318 inches and 0.322 inches

Collarheight:

Between 0.437 inches and 0.457 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Collar Inside Diameter:

Between 0.208 inches and 0.212 inches

End Application:

1520-01-457-5179

Grip Length:

Between 0.365 inches and 0.385 inches

Width Across Flats:

Between 0.332 inches and 0.342 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

10.0 inches

Shear Strength:

6130 double pounds per square inch

Countersink Angle:

100.0 degrees

Collar Style:

Threaded break off type

Product Name:

Pin collar assembly

Heat Treatment:

T-6 solution heat treated collar

Material:

Titanium alloy body

Material Specification:

Qq-a-430 or qq-a-225/6 federal specification single material response collar

Surface Treatment:

Anodize collar

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response collar

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.