

View Online at <https://aerobasegroup.com/nsn/5320-01-607-1782>

Thread Class:

3a

Fastener Length:

1.020 inches

Head Style:

Straight pan

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.122 inches and 0.142 inches

Shank Diameter:

Between 0.2641 inches and 0.2651 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.337 inches and 0.412 inches

Collar Outside Diameter:

Between 0.418 inches and 0.422 inches

Collarheight:

Between 0.532 inches and 0.552 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Collar Inside Diameter:

Between 0.268 inches and 0.272 inches

End Application:

1520-01-457-5179

Grip Length:

0.625 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

4300 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

10490 double pounds per square inch

Collar Style:

Threaded break off type

Product Name:

Pin collar assembly

Heat Treatment:

T-6 solution heat treated collar

Material:

Titanium alloy uns r56400 bolt

Material Specification:

Qq-a-430 federal specification single material response or qq0a-225/6 federal specification single material response collar

Surface Treatment:

Anodize collar

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response collar

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.