

View Online at <https://aerobasegroup.com/nsn/5320-01-607-1782>

**Thread Class:**

3a

**Fastener Length:**

1.020 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.059 inches and 0.069 inches

**Width Between Flats:**

Between 0.122 inches and 0.142 inches

**Shank Diameter:**

Between 0.2641 inches and 0.2651 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.337 inches and 0.412 inches

**Collar Outside Diameter:**

Between 0.418 inches and 0.422 inches

**Collarheight:**

Between 0.532 inches and 0.552 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Collar Inside Diameter:**

Between 0.268 inches and 0.272 inches

**End Application:**

1520-01-457-5179

**Grip Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

4300 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

10490 double pounds per square inch

**Collar Style:**

Threaded break off type

**Product Name:**

Pin collar assembly

**Heat Treatment:**

T-6 solution heat treated collar

**Material:**

Titanium alloy uns r56400 bolt

**Material Specification:**

Qq-a-430 federal specification single material response or qq0a-225/6 federal specification single material response collar

**Surface Treatment:**

Anodize collar

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response collar

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-a-8625 spec.