

View Online at <https://aerobasegroup.com/nsn/5320-01-607-1789>

Thread Class:

3b

Thread Direction:

Right-hand

Identification Code Color:

Red

Fastener Length:

Between 0.885 inches and 0.905 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.122 inches and 0.142 inches

Shank Diameter:

Between 0.2646 inches and 0.2651 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Collar Outside Diameter:

Between 0.418 inches and 0.422 inches

Collarheight:

Between 0.532 inches and 0.552 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Collar Inside Diameter:

Between 0.268 inches and 0.272 inches

End Application:

1520-01-457-5179

Grip Length:

Between 0.495 inches and 0.505 inches

Width Across Flats:

Between 0.0947 inches and 0.0967 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.25 inches

Shear Strength:

10490 double pounds per square inch

Countersink Angle:

90.0 degrees

Collar Style:

Threaded break off type

Product Name:

Protruding shear head titanium 1/16 grip variation-1/64 oversize hi-l

Heat Treatment:

T-6 solution heat treated collar

Material:

Titanium alloy bolt

Material Specification:

Qq-a-430 or qq-a-225/6 federal specification single material response collar

Surface Treatment:

Anodize collar

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response collar

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.