## NSN 5320-01-607-7774

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-607-7774 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.4687 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2564 inches and 0.2612 inches Tip Diameter: Between 0.1570 inches and 0.1595 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** B-2 bomber **Grip Length:** Between 0.1825 inches and 0.1925 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 8.0 inches **Shear Strength:** 4010 double pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** 100 degree flush shear head Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** 

Aluminum

**Surface Treatment Specification:** 

Hi-shearspec.294 mfr ref single treatment response

## NSN 5320-01-607-7774

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A528u0