

View Online at <https://aerobasegroup.com/nsn/5320-01-608-3392>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.375 inches and 1.395 inches

Head Style:

Straight pan

Head Height:

Between 0.093 inches and 0.105 inches

Width Between Flats:

Between 0.233 inches and 0.253 inches

Shank Diameter:

Between 0.4365 inches and 0.4370 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.641 inches and 0.676 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

B-1 aircraft

Grip Length:

Between 0.745 inches and 0.755 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.4375 inches

Shear Strength:

37500 double pounds per square inch

Product Name:

Protruding shear head

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear spec. 258 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0