

View Online at <https://aerobasegroup.com/nsn/5320-01-611-4849>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.535 inches and 0.555 inches

Head Style:

Flush countersunk

Head Height:

Between 0.0693 inches and 0.0714 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3891 inches and 0.3901 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.5554 inches and 0.5604 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.245 inches and 0.255 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel bolt

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ms-qq-p-416, type ii, class ii national specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0