NSN 5320-01-612-2985



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-612-2985 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.107 inches **Head Style:** Straight pan **Head Height:** Between 0.078 inches and 0.088 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.197 inches and 0.217 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.585 inches and 0.600 inches **Grip Length:** 0.562 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 24600 double pounds per square inch Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5628 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

No

Unit Of Measure:

Demilitarization:

N/a

NSN 5320-01-612-2985

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.