

View Online at <https://aerobasegroup.com/nsn/5320-01-612-3150>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.420 inches

Head Style:

Straight pan

Head Height:

Between 0.130 inches and 0.140 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.197 inches and 0.217 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.550 inches and 0.585 inches

Grip Length:

0.875 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Shear Strength:

24600 double pounds per square inch

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-6049 military specification single material response or ams 6322 assn standard single material response or ams6382 assn standard single material response or ams6415 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Aqq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.