

View Online at <https://aerobasegroup.com/nsn/5320-01-612-3306>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.545 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.130 inches and 0.140 inches

**Width Between Flats:**

Between 0.1582 inches and 0.1617 inches

**Shank Diameter:**

Between 0.197 inches and 0.217 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.550 inches and 0.585 inches

**Grip Length:**

1.000 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Shear Strength:**

24600 double pounds per square inch

**Material:**

Steel comp 8740 or steel comp 4140 or steel comp 4340

**Material Specification:**

Mil-s-6049 military specification single material response or ams 6322 assn standard single material response or ams 6382 assn standard single material response or ams 6415 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.